


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:240.0V I:0.0642A P:14.32W PF:0.9294 Lamp Flux:1189.25x1 lm		
NAME: DEEP DOWN MINI_WHT_SLE G7 09mm_350mA_4000K CRI90_32 DEG		
MFR.: DARKON		

DATA OF LAMP		PHOTOMETRIC DATA Eff: 83.06 lm/W			
MODEL	SLE G7 09mm 1200lm	Imax(cd)	1365	S/MH(C0/180)	0.81
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	0.87
RATED VOLTAGE(V)	230.0	TOTAL FLUX(lm)	1189.2	η UP,DN(C0-180)	0.0,50.2
NOMINAL FLUX(lm)	1189.25	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,49.8
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	0.75
TEST VOLTAGE(V)	230	η down(%)	100.0	CIBSE SHR MAX	0.90

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:23 February 2023

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.995m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	1305	1283	1260	1246	1230	1250	1296	1311	0- 10	126.1	126.1	10.6,10.6
20	983.8	940.6	926.8	899.5	865.6	878.9	949.7	1005	10- 20	308.4	434.5	36.5,36.5
30	656.4	625.1	608.6	590.8	591.4	605.6	637.8	674.8	20- 30	358.7	793.2	66.7,66.7
40	144.9	144.5	144.6	139.3	136.6	137.1	139.8	147.1	30- 40	193.2	986.3	82.9,82.9
50	80.17	81.25	80.48	78.95	77.65	76.67	77.10	79.31	40- 50	83.99	1070	90,90
60	38.84	39.50	39.87	40.15	39.65	38.54	37.95	38.16	50- 60	51.19	1122	94.3,94.3
70	30.21	30.92	31.40	31.50	30.83	29.78	29.37	29.61	60- 70	34.84	1156	97.2,97.2
80	16.04	16.75	16.95	16.65	15.96	15.18	15.02	15.42	70- 80	24.64	1181	99.3,99.3
90	0.1565	0.1164	0.0983	0.1712	0.1965	0.1273	0.1310	0.1275	80- 90	8.247	1189	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1032.6 lm

%lum = 86.8%

%lamp = 86.8%

Conical surface Flux(120deg): 1121.5 lm

%lum = 94.3%


%lamp = 94.3%

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:23 February 2023

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.995m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:240.0V I:0.0642A P:14.32W PF:0.9294 Lamp Flux:1189.25x1 lm		
NAME: DEEP DOWN MINI_WHT_SLE G7 09mm_350mA_4000K CRI90_32 DEG		
MFR.: DARKON		



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	70623	72348
80	71078	75133
75	69375	72572
70	67973	70655
65	63498	66003
60	59773	61363
55	78032	78573
50	95978	96358
45	120189	120996


C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JEFF
 Test Date: 23 February 2023

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity: 65.0%
 Test Distance: 7.995m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:240.0V I:0.0642A P:14.32W PF:0.9294 Lamp Flux:1189.25x1 lm		
NAME: DEEP DOWN MINI_WHT_SLE G7 09mm_350mA_4000K CRI90_32 DEG		
MFR.: DARKON		

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.09	1.06	1.04	1.07	1.04	1.02	1.03	1.01	.99	.99	.98	.96	.96	.94	.93	.91
2.0	1.01	.96	.92	.99	.95	.91	.95	.92	.89	.92	.90	.87	.90	.87	.85	.83
3.0	.93	.87	.83	.92	.86	.82	.89	.84	.81	.86	.83	.80	.84	.81	.78	.77
4.0	.86	.80	.76	.85	.79	.75	.83	.78	.74	.81	.77	.73	.79	.75	.72	.71
5.0	.80	.74	.69	.79	.74	.69	.78	.72	.68	.76	.71	.68	.74	.70	.67	.66
6.0	.75	.69	.64	.74	.68	.64	.73	.68	.64	.71	.67	.63	.70	.66	.63	.61
7.0	.71	.64	.60	.70	.64	.60	.69	.63	.59	.67	.63	.59	.66	.62	.59	.57
8.0	.66	.60	.56	.66	.60	.56	.65	.59	.55	.64	.59	.55	.63	.58	.55	.53
9.0	.63	.57	.52	.62	.56	.52	.61	.56	.52	.60	.55	.52	.59	.55	.52	.50
10.0	.59	.53	.49	.59	.53	.49	.58	.53	.49	.57	.52	.49	.57	.52	.49	.47



C Range: 0 - 360DEG

C Interval: 22.5DEG

Test Speed: HIGH

Temperature:25.3DEG

Operators:JEFF

Test Date:23 February 2023

γ Range: 0 - 90DEG

γ Interval: 1.0DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295

Humidity:65.0%

Test Distance:7.995m [K=1.0000]

Remarks:

WEC AND CCEC

Test:U:240.0V I:0.0642A P:14.32W PF:0.9294 Lamp Flux:1189.25x1 lm		
NAME: DEEP DOWN MINI_WHT_SLE G7 09mm_350mA_4000K CRI90_32 DEG		
MFR.: DARKON		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)									
0.0																
1.0	.207	.118	.037	.200	.114	.036	.187	.107	.034	.176	.101	.032	.165	.095	.031	
2.0	.195	.107	.033	.189	.104	.032	.178	.099	.031	.168	.094	.030	.159	.090	.028	
3.0	.183	.097	.029	.178	.095	.029	.169	.091	.028	.160	.088	.027	.152	.084	.026	
4.0	.172	.089	.026	.168	.088	.026	.160	.085	.025	.152	.082	.025	.145	.079	.024	
5.0	.162	.083	.024	.158	.081	.024	.151	.079	.023	.145	.076	.023	.139	.074	.022	
6.0	.153	.077	.022	.150	.076	.022	.144	.074	.021	.138	.072	.021	.132	.070	.021	
7.0	.145	.072	.020	.142	.071	.020	.137	.069	.020	.131	.067	.020	.127	.066	.019	
8.0	.138	.067	.019	.135	.067	.019	.130	.065	.019	.126	.064	.018	.121	.062	.018	
9.0	.131	.063	.018	.129	.063	.018	.124	.062	.017	.120	.060	.017	.116	.059	.017	
10.0	.125	.060	.017	.123	.059	.017	.119	.058	.016	.115	.057	.016	.112	.056	.016	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.173	.157	.143	.148	.135	.123	.101	.093	.085	.058	.054	.049	.019	.017	.016	
2.0	.159	.132	.110	.136	.114	.095	.094	.079	.066	.054	.046	.039	.017	.015	.013	
3.0	.148	.114	.087	.127	.098	.075	.087	.068	.053	.050	.040	.031	.016	.013	.010	
4.0	.138	.099	.070	.118	.086	.061	.081	.060	.043	.047	.035	.025	.015	.011	.008	
5.0	.129	.088	.057	.111	.076	.050	.076	.053	.035	.044	.031	.021	.014	.010	.007	
6.0	.122	.079	.048	.105	.068	.042	.072	.048	.029	.042	.028	.018	.014	.009	.006	
7.0	.115	.071	.041	.099	.062	.035	.068	.043	.025	.040	.026	.015	.013	.008	.005	
8.0	.109	.065	.035	.094	.056	.030	.065	.040	.022	.038	.023	.013	.012	.008	.004	
9.0	.104	.060	.030	.089	.052	.026	.062	.037	.019	.036	.022	.011	.012	.007	.004	
10.0	.099	.056	.027	.085	.048	.023	.059	.034	.016	.035	.020	.010	.011	.007	.003	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:23 February 2023

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.995m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:240.0V I:0.0642A P:14.32W PF:0.9294 Lamp Flux:1189.25x1 lm										
NAME: DEEP DOWN MINI_WHT_SLE G7 09mm_350mA_4000K						CRI90_32 DEG				
MFR.: DARKON										
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	25.5	26.6	25.7	26.7	26.9	25.4	26.5	25.7	26.7	26.8
3H	26.3	27.3	26.6	27.5	27.7	26.3	27.3	26.6	27.5	27.7
4H	26.8	27.7	27.1	28.0	28.2	26.9	27.8	27.1	28.0	28.2
6H	27.3	28.1	27.6	28.4	28.6	27.4	28.2	27.7	28.5	28.7
8H	27.5	28.3	27.8	28.6	28.8	27.6	28.4	27.9	28.7	28.9
12H	27.6	28.4	27.9	28.7	29.0	27.7	28.5	28.1	28.8	29.1
4H 2H	25.7	26.6	26.0	26.8	27.1	25.6	26.6	25.9	26.8	27.0
3H	26.8	27.6	27.1	27.9	28.2	26.8	27.6	27.2	27.9	28.2
4H	27.5	28.2	27.8	28.5	28.8	27.5	28.3	27.9	28.6	28.9
6H	28.1	28.8	28.5	29.1	29.5	28.2	28.9	28.6	29.2	29.6
8H	28.4	29.0	28.8	29.4	29.7	28.5	29.1	28.9	29.5	29.8
12H	28.6	29.2	29.0	29.5	29.9	28.7	29.3	29.1	29.7	30.0
8H 4H	27.8	28.4	28.2	28.7	29.1	27.8	28.4	28.2	28.8	29.1
6H	28.6	29.1	29.0	29.5	29.9	28.7	29.2	29.1	29.6	30.0
8H	29.0	29.4	29.4	29.8	30.3	29.1	29.5	29.5	29.9	30.4
12H	29.3	29.6	29.7	30.1	30.6	29.4	29.8	29.9	30.2	30.7
12H 4H	27.8	28.3	28.2	28.7	29.1	27.8	28.4	28.2	28.7	29.1
6H	28.7	29.1	29.1	29.5	30.0	28.7	29.2	29.2	29.6	30.0
8H	29.1	29.5	29.6	29.9	30.4	29.2	29.6	29.7	30.0	30.5
Variations with the observer position at spacings:										
S = 1.0H	+ 0.3 / - 0.4					+ 0.3 / - 0.4				
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H	+ 0.7 / - 0.6					+ 0.7 / - 0.5				

CIE Pub.117 Corrected 1189 lm Total Lamp Luminous Flux. (8log(F/F0) = 0.6)

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:23 February 2023

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.995m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:240.0V I:0.0642A P:14.32W PF:0.9294 Lamp Flux:1189.25x1 lm		
NAME: DEEP DOWN MINI_WHT_SLE G7 09mm_350mA_4000K CRI90_32 DEG		
MFR.: DARKON		


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	81	74	69	80	73	69	80	73	69	65
0.80	89	82	77	88	82	77	87	81	77	73
1.00	94	87	83	93	87	83	92	87	82	78
1.25	99	92	88	98	92	88	96	91	87	82
1.50	102	96	92	101	95	92	98	94	90	85
2.00	106	100	97	104	99	96	101	97	94	88
2.50	108	103	99	106	102	98	103	99	97	90
3.00	110	105	102	108	104	101	104	101	99	92
4.00	112	109	106	110	107	104	106	104	102	94
5.00	114	111	108	111	109	107	107	105	104	96
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JEFF
Test Date: 23 February 2023

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity: 65.0%
Test Distance: 7.995m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:240.0V I:0.0642A P:14.32W PF:0.9294 Lamp Flux:1189.25x1 lm		
NAME: DEEP DOWN MINI_WHT_SLE G7 09mm_350mA_4000K CRI90_32 DEG		
MFR.: DARKON		




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:23 February 2023

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.995m [K=1.0000]
Remarks:

AAI Figure

Test:U:240.0V I:0.0642A P:14.32W PF:0.9294 Lamp Flux:1189.25x1 lm		
NAME: DEEP DOWN MINI_WHT_SLE G7 09mm_350mA_4000K CRI90_32 DEG		
MFR.: DARKON		




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JEFF
Test Date: 23 February 2023

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity: 65.0%
Test Distance: 7.995m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:240.0V I:0.0642A P:14.32W PF:0.9294 Lamp Flux:1189.25x1 lm		
NAME: DEEP DOWN MINI_WHT_SLE G7 09mm_350mA_4000K CRI90_32 DEG		
MFR.: DARKON		



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:23 February 2023

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.995m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:240.0V I:0.0642A P:14.32W PF:0.9294 Lamp Flux:1189.25x1 lm		
NAME: DEEP DOWN MINI_WHT_SLE G7 09mm_350mA_4000K CRI90_32 DEG		
MFR.: DARKON		


AvgL	cd/m2
L_0~180 (65) av	64649
L_0~180 (75) av	69581
L_0~180 (85) av	67723
L_90~270 (65) av	64269
L_90~270 (75) av	69410
L_90~270 (85) av	67527
L_45 (65) av	64462
L_45 (75) av	69527
L_45 (85) av	67602

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:23 February 2023

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.995m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JEFF
Test Date: 23 February 2023

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity: 65.0%
Test Distance: 7.995m [K=1.0000]
Remarks:

