


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:239.9V I:0.0688A P:15.49W PF:0.9383 Lamp Flux:1658.57x1 lm		
NAME: BARREL_WHT_10 DEG_350mA_3000K CRI80	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 107.07 lm/W			
MODEL	TRIDONIC SLE G7 09MM	Imax(cd)	15207	S/MH(C0/180)	0.29
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	0.30
RATED VOLTAGE(V)	230.0	TOTAL FLUX(lm)	1658.6	η UP,DN(C0-180)	0.0,49.8
NOMINAL FLUX(lm)	1658.57	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,50.2
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	0.00
TEST VOLTAGE(V)	230	η down(%)	100.0	CIBSE SHR MAX	1.00

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:13 January 2023

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.995m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	633.0	584.0	565.9	564.9	562.4	608.8	630.3	632.3	0- 10	962.0	962.0	58,58
20	44.59	43.30	42.76	40.37	36.46	37.81	38.18	39.55	10- 20	496.2	1458	87.9,87.9
30	11.52	11.06	10.67	10.31	10.40	10.53	11.07	11.48	20- 30	92.79	1551	93.5,93.5
40	4.991	5.019	4.784	4.689	4.660	4.721	4.776	4.932	30- 40	45.95	1597	96.3,96.3
50	2.351	2.400	2.310	2.257	2.292	2.165	2.166	2.231	40- 50	25.67	1623	97.8,97.8
60	1.410	1.458	1.397	1.366	1.396	1.368	1.361	1.389	50- 60	15.72	1638	98.8,98.8
70	0.9420	0.9498	0.8960	0.8529	0.8693	0.8724	0.9024	0.9474	60- 70	11.47	1650	99.5,99.5
80	0.4034	0.3924	0.3718	0.3527	0.3559	0.3671	0.3891	0.4074	70- 80	6.896	1657	99.9,99.9
90	0.0062	0.0044	0.0040	0.0036	0.0044	0.0044	0.0047	0.0066	80- 90	1.850	1659	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY: μ A10cd									UNIT:lm		

Conical surface Flux(90deg): 1611.7 lm

%lum = 97.2%

%lamp = 97.2%

Conical surface Flux(120deg): 1638.4 lm

%lum = 98.8%


%lamp = 98.8%

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:13 January 2023

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.995m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:239.9V I:0.0688A P:15.49W PF:0.9383 Lamp Flux:1658.57x1 lm		
NAME: BARREL_WHT_10 DEG_350mA_3000K CRI80	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	8388	7287
80	9669	8924
75	11172	10727
70	11464	10919
65	11656	11318
60	11739	11642
55	12870	12488
50	15224	14978
45	19784	19312


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:13 January 2023

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.995m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:239.9V I:0.0688A P:15.49W PF:0.9383 Lamp Flux:1658.57x1 lm		
NAME: BARREL_WHT_10 DEG_350mA_3000K CRI80	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.13	1.12	1.10	1.11	1.10	1.08	1.07	1.06	1.05	1.04	1.03	1.02	1.00	.00	.99	.97
2.0	1.09	1.06	1.04	1.07	1.05	1.03	1.04	1.02	1.00	1.01	.00	.98	.99	.97	.96	.95
3.0	1.05	1.02	.99	1.04	1.01	.98	1.01	.99	.97	.99	.97	.95	.97	.95	.94	.93
4.0	1.02	.98	.95	1.00	.97	.95	.99	.96	.94	.97	.95	.93	.95	.93	.92	.91
5.0	.99	.95	.92	.98	.95	.92	.96	.93	.91	.95	.92	.91	.94	.91	.90	.89
6.0	.96	.93	.90	.96	.92	.90	.94	.91	.89	.93	.91	.89	.92	.90	.88	.87
7.0	.94	.90	.88	.93	.90	.88	.92	.89	.87	.91	.89	.87	.91	.88	.87	.86
8.0	.92	.89	.86	.92	.88	.86	.91	.88	.86	.90	.87	.85	.89	.87	.85	.84
9.0	.90	.87	.85	.90	.87	.84	.89	.86	.84	.88	.86	.84	.88	.85	.84	.83
10.0	.89	.85	.83	.88	.85	.83	.88	.85	.83	.87	.85	.83	.87	.84	.83	.82



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:13 January 2023

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.995m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:239.9V I:0.0688A P:15.49W PF:0.9383 Lamp Flux:1658.57x1 lm		
NAME: BARREL_WHT_10 DEG_350mA_3000K CRI80	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.127	.072	.023	.121	.069	.022	.109	.062	.020	.097	.056	.018	.087	.050	.016		
2.0	.116	.064	.020	.111	.061	.019	.101	.056	.017	.092	.051	.016	.083	.047	.015		
3.0	.107	.057	.017	.102	.055	.017	.094	.051	.015	.086	.047	.015	.079	.044	.014		
4.0	.099	.051	.015	.095	.050	.015	.088	.047	.014	.081	.044	.013	.075	.041	.012		
5.0	.092	.047	.014	.089	.045	.013	.083	.043	.013	.077	.041	.012	.072	.038	.012		
6.0	.086	.043	.012	.083	.042	.012	.078	.040	.012	.073	.038	.011	.069	.036	.011		
7.0	.080	.040	.011	.078	.039	.011	.074	.037	.011	.070	.036	.010	.066	.034	.010		
8.0	.076	.037	.010	.074	.036	.010	.070	.035	.010	.067	.034	.010	.063	.032	.009		
9.0	.072	.035	.010	.070	.034	.010	.067	.033	.009	.064	.032	.009	.061	.031	.009		
10.0	.068	.033	.009	.067	.032	.009	.064	.031	.009	.061	.030	.009	.058	.029	.008		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)										
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020		
1.0	.168	.158	.149	.143	.135	.128	.098	.093	.089	.056	.054	.052	.018	.017	.017		
2.0	.149	.133	.119	.127	.114	.103	.087	.079	.072	.050	.046	.042	.016	.015	.014		
3.0	.133	.113	.097	.114	.098	.084	.078	.068	.059	.045	.040	.035	.015	.013	.011		
4.0	.120	.098	.081	.103	.084	.070	.071	.059	.049	.041	.034	.029	.013	.011	.010		
5.0	.108	.085	.068	.093	.074	.059	.064	.051	.042	.037	.030	.025	.012	.010	.008		
6.0	.099	.075	.058	.085	.065	.050	.059	.045	.035	.034	.027	.021	.011	.009	.007		
7.0	.091	.066	.049	.078	.058	.043	.054	.040	.030	.031	.024	.018	.010	.008	.006		
8.0	.084	.059	.043	.072	.052	.037	.050	.036	.026	.029	.021	.016	.009	.007	.005		
9.0	.078	.054	.037	.067	.046	.033	.046	.033	.023	.027	.019	.014	.009	.006	.005		
10.0	.072	.049	.033	.062	.042	.029	.043	.030	.020	.025	.018	.012	.008	.006	.004		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:13 January 2023

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.995m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:239.9V I:0.0688A P:15.49W PF:0.9383 Lamp Flux:1658.57x1 lm										
NAME: BARREL_WHT_10 DEG_350mA_3000K CRI80					TYPE:LED			WEIGHT:		
SPEC.:					DIM.:			SERIAL No.:1		
MFR.: DARKON					SUR.:			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	13.5	14.1	13.7	14.2	14.3	13.6	14.2	13.8	14.3	14.5
3H	14.6	15.1	14.8	15.3	15.5	14.7	15.2	14.9	15.4	15.6
4H	15.1	15.6	15.4	15.8	16.0	15.2	15.7	15.5	15.9	16.1
6H	15.5	16.0	15.8	16.2	16.5	15.6	16.0	15.8	16.3	16.5
8H	15.6	16.1	15.9	16.3	16.6	15.6	16.1	15.9	16.3	16.6
12H	15.7	16.1	16.0	16.4	16.7	15.7	16.1	16.0	16.4	16.6
4H 2H	13.9	14.4	14.2	14.6	14.8	14.1	14.6	14.3	14.8	15.0
3H	15.3	15.7	15.6	16.0	16.2	15.4	15.8	15.7	16.1	16.3
4H	15.9	16.3	16.3	16.6	16.9	16.0	16.4	16.4	16.7	17.0
6H	16.4	16.8	16.8	17.1	17.5	16.5	16.8	16.8	17.2	17.5
8H	16.6	16.9	16.9	17.3	17.6	16.6	16.9	16.9	17.3	17.6
12H	16.6	17.0	17.0	17.3	17.7	16.6	16.9	17.0	17.3	17.7
8H 4H	16.1	16.5	16.5	16.8	17.2	16.2	16.6	16.6	16.9	17.3
6H	16.8	17.1	17.2	17.4	17.8	16.8	17.1	17.2	17.5	17.9
8H	16.9	17.2	17.4	17.6	18.1	16.9	17.2	17.4	17.6	18.0
12H	17.1	17.3	17.6	17.8	18.2	17.0	17.3	17.5	17.7	18.2
12H 4H	16.1	16.5	16.5	16.8	17.2	16.2	16.5	16.6	16.9	17.3
6H	16.8	17.0	17.2	17.4	17.9	16.8	17.0	17.2	17.5	17.9
8H	17.0	17.2	17.5	17.7	18.1	17.0	17.2	17.4	17.6	18.1
Variations with the observer position at spacings:										
S = 1.0H	+ 0.4 / - 0.5					+ 0.4 / - 0.6				
1.5H	+ 0.7 / - 0.5					+ 0.7 / - 0.6				
2.0H	+ 0.7 / - 0.5					+ 0.7 / - 0.7				

CIE Pub.117 Corrected 1659 lm Total Lamp Luminous Flux. (8log(F/F0) = 1.8)

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:13 January 2023

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.995m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:239.9V I:0.0688A P:15.49W PF:0.9383 Lamp Flux:1658.57x1 lm		
NAME: BARREL_WHT_10 DEG_350mA_3000K CRI80	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	89	83	80	89	83	80	88	83	79	76
0.80	96	91	87	96	91	87	95	90	87	83
1.00	100	95	92	100	95	91	98	94	91	87
1.25	104	99	96	103	99	95	101	97	95	91
1.50	107	102	99	105	101	98	103	100	97	93
2.00	109	105	102	108	104	101	105	102	100	95
2.50	111	107	104	109	106	103	106	103	101	96
3.00	112	109	106	110	107	105	107	105	103	97
4.00	114	111	109	112	110	108	108	107	105	98
5.00	115	113	111	113	111	110	109	108	107	99
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JEFF
 Test Date: 13 January 2023

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity: 65.0%
 Test Distance: 7.995m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:239.9V I:0.0688A P:15.49W PF:0.9383 Lamp Flux:1658.57x1 lm		
NAME: BARREL_WHT_10 DEG_350mA_3000K CRI80	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:13 January 2023

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.995m [K=1.0000]
Remarks:

AAI Figure

Test:U:239.9V I:0.0688A P:15.49W PF:0.9383 Lamp Flux:1658.57x1 lm		
NAME: BARREL_WHT_10 DEG_350mA_3000K CRI80	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:13 January 2023

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.995m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:239.9V I:0.0688A P:15.49W PF:0.9383 Lamp Flux:1658.57x1 lm		
NAME: BARREL_WHT_10 DEG_350mA_3000K CRI80	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:13 January 2023

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.995m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:239.9V I:0.0688A P:15.49W PF:0.9383 Lamp Flux:1658.57x1 lm		
NAME: BARREL_WHT_10 DEG_350mA_3000K CRI80	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	11430
L_0~180 (75) av	10700
L_0~180 (85) av	7819
L_90~270 (65) av	11287
L_90~270 (75) av	10642
L_90~270 (85) av	7876
L_45 (65) av	11405
L_45 (75) av	10701
L_45 (85) av	7862

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:13 January 2023

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.995m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JEFF
Test Date: 13 January 2023

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity: 65.0%
Test Distance: 7.995m [K=1.0000]
Remarks:

