


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:240.0V I:0.1615A P:37.11W PF:0.9577 Lamp Flux:3427.48x1 lm		
NAME: FLATLINE_1296_SUS_WHT_UPLIGHT_OPAL V_HE_500mA_4000K CRI90	WEIGHT:	
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 92.35 lm/W			
LED MODULE	1300lm 940 HV ADV5	Imax(cd)	1292	S/MH(C0/180)	1.22
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.19
RATED VOLTAGE(V)	230.0	TOTAL FLUX(lm)	3427.5	η UP,DN(C0-180)	0.0,50.1
NOMINAL FLUX(lm)	3427.48	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,49.9
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	230	η down(%)	100.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:31 August 2023

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.892m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	1262	1261	1261	1264	1265	1262	1258	1259	0- 10	121.9	121.9	3.56,3.56
20	1187	1178	1171	1179	1183	1175	1165	1174	10- 20	345.5	467.4	13.6,13.6
30	1050	1044	1034	1046	1055	1041	1027	1039	20- 30	513.1	980.5	28.6,28.6
40	889.7	877.4	867.6	882.5	895.3	877.8	861.2	873.3	30- 40	602.5	1583	46.2,46.2
50	710.6	695.8	684.4	700.0	713.5	695.8	679.4	692.4	40- 50	609.2	2192	64,64
60	517.1	504.5	494.5	506.1	517.8	504.2	491.6	502.5	50- 60	537.5	2730	79.6,79.6
70	319.1	311.3	306.0	311.0	324.1	310.3	305.0	310.6	60- 70	403.4	3133	91.4,91.4
80	129.0	132.1	133.0	130.1	124.0	130.7	133.2	132.5	70- 80	230.7	3364	98.1,98.1
90	1.034	4.752	6.126	4.347	0.9681	2.831	4.061	3.273	80- 90	63.70	3427	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1892 lm

%lum = 55.2%

%lamp = 55.2%

Conical surface Flux(120deg): 2729.7 lm

%lum = 79.6%


%lamp = 79.6%

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:31 August 2023

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.892m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:240.0V I:0.1615A P:37.11W PF:0.9577 Lamp Flux:3427.48x1 lm		
NAME: FLATLINE_1296_SUS_WHT_UPLIGHT_OPAL V_HE_500mA 4000K CRI90	WEIGHT:	
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JEFF
Test Date: 31 August 2023

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity: 65.0%
Test Distance: 7.892m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:240.0V I:0.1615A P:37.11W PF:0.9577 Lamp Flux:3427.48x1 lm		
NAME: FLATLINE_1296_SUS_WHT_UPLIGHT_OPAL V_HE_500mA_4000K CRI90		WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.04	.00	.96	1.02	.98	.94	.98	.94	.91	.94	.91	.89	.90	.88	.86	.84
2.0	.91	.84	.78	.89	.83	.77	.85	.80	.76	.82	.78	.74	.79	.76	.72	.70
3.0	.80	.72	.65	.78	.71	.65	.75	.69	.64	.73	.67	.63	.70	.65	.61	.59
4.0	.71	.62	.56	.70	.61	.55	.67	.60	.54	.65	.59	.54	.63	.57	.53	.51
5.0	.63	.55	.48	.62	.54	.48	.60	.53	.47	.58	.52	.47	.56	.51	.46	.44
6.0	.57	.48	.42	.56	.48	.42	.54	.47	.41	.53	.46	.41	.51	.45	.41	.39
7.0	.52	.43	.37	.51	.43	.37	.50	.42	.37	.48	.41	.36	.47	.41	.36	.34
8.0	.47	.39	.33	.47	.39	.33	.45	.38	.33	.44	.38	.33	.43	.37	.32	.31
9.0	.44	.35	.30	.43	.35	.30	.42	.35	.30	.41	.34	.29	.40	.34	.29	.28
10.0	.40	.32	.27	.40	.32	.27	.39	.32	.27	.38	.31	.27	.37	.31	.27	.25



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:31 August 2023

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.892m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:240.0V I:0.1615A P:37.11W PF:0.9577 Lamp Flux:3427.48x1 lm		
NAME: FLATLINE_1296_SUS_WHT_UPLIGHT_OPAL V_HE_500mA_4000K CRI90	WEIGHT:	
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.305	.174	.055	.298	.170	.054	.285	.164	.052	.273	.157	.051	.262	.152	.049		
2.0	.287	.158	.048	.281	.155	.048	.270	.150	.047	.259	.145	.045	.249	.141	.044		
3.0	.266	.142	.042	.261	.140	.042	.250	.136	.041	.241	.132	.040	.232	.129	.040		
4.0	.246	.128	.038	.241	.126	.037	.232	.123	.037	.224	.120	.036	.216	.117	.036		
5.0	.228	.116	.034	.223	.115	.033	.215	.112	.033	.208	.110	.033	.201	.107	.032		
6.0	.211	.106	.030	.207	.105	.030	.200	.103	.030	.193	.101	.030	.187	.099	.029		
7.0	.197	.097	.028	.193	.096	.027	.187	.094	.027	.181	.093	.027	.175	.091	.027		
8.0	.184	.090	.025	.181	.089	.025	.175	.087	.025	.170	.086	.025	.165	.084	.025		
9.0	.172	.083	.023	.170	.083	.023	.165	.081	.023	.160	.080	.023	.155	.079	.023		
10.0	.162	.078	.022	.160	.077	.022	.155	.076	.021	.151	.075	.021	.147	.074	.021		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.180	.156	.135	.154	.134	.116	.105	.092	.080	.061	.053	.047	.019	.017	.015	
2.0	.172	.132	.099	.147	.114	.085	.101	.079	.059	.058	.046	.035	.019	.015	.011	
3.0	.164	.114	.075	.140	.099	.065	.096	.068	.046	.056	.040	.027	.018	.013	.009	
4.0	.156	.101	.059	.134	.087	.051	.092	.061	.036	.053	.036	.021	.017	.012	.007	
5.0	.149	.090	.048	.128	.078	.041	.088	.055	.029	.051	.032	.017	.016	.010	.006	
6.0	.141	.082	.039	.122	.071	.034	.084	.050	.024	.049	.029	.014	.016	.010	.005	
7.0	.135	.075	.033	.116	.065	.029	.080	.046	.021	.046	.027	.012	.015	.009	.004	
8.0	.128	.069	.029	.110	.060	.025	.076	.042	.018	.044	.025	.011	.014	.008	.004	
9.0	.122	.064	.025	.105	.056	.022	.073	.039	.016	.042	.023	.009	.014	.008	.003	
10.0	.117	.060	.023	.100	.052	.020	.070	.037	.014	.041	.022	.008	.013	.007	.003	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:31 August 2023

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.892m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:240.0V I:0.1615A P:37.11W PF:0.9577 Lamp Flux:3427.48x1 lm											
NAME: FLATLINE_1296_SUS_WHT_UPLIGHT_OPAL V_HE_500mA_4000K CRI90								WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:1			
MFR.: DARKON					SUR.:			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	2H	23.8	25.3	24.1	25.5	25.8	23.7	25.2	23.9	25.4	25.6
	3H	25.3	26.7	25.6	26.9	27.2	25.1	26.5	25.4	26.7	27.0
	4H	25.9	27.2	26.2	27.5	27.7	25.7	27.0	26.0	27.3	27.5
	6H	26.3	27.5	26.6	27.8	28.1	26.1	27.4	26.5	27.7	27.9
	8H	26.4	27.6	26.8	27.9	28.2	26.3	27.5	26.6	27.8	28.1
	12H	26.5	27.6	26.8	27.9	28.2	26.4	27.5	26.7	27.8	28.1
4H	2H	24.4	25.7	24.7	26.0	26.2	24.3	25.6	24.6	25.8	26.1
	3H	26.1	27.2	26.4	27.5	27.8	25.9	27.1	26.3	27.4	27.7
	4H	26.8	27.8	27.2	28.2	28.5	26.6	27.7	27.0	28.0	28.3
	6H	27.3	28.3	27.7	28.6	29.0	27.2	28.1	27.6	28.5	28.8
	8H	27.5	28.4	27.9	28.7	29.1	27.4	28.3	27.8	28.6	29.0
	12H	27.6	28.4	28.0	28.8	29.2	27.5	28.3	28.0	28.7	29.1
8H	4H	27.0	27.9	27.5	28.3	28.7	26.9	27.8	27.3	28.1	28.5
	6H	27.7	28.4	28.2	28.8	29.3	27.6	28.3	28.1	28.7	29.2
	8H	28.0	28.6	28.4	29.0	29.5	27.9	28.6	28.4	29.0	29.4
	12H	28.1	28.7	28.6	29.1	29.6	28.1	28.7	28.6	29.1	29.6
12H	4H	27.1	27.9	27.5	28.2	28.6	26.9	27.7	27.3	28.1	28.5
	6H	27.8	28.4	28.2	28.8	29.3	27.7	28.3	28.1	28.7	29.2
	8H	28.1	28.6	28.5	29.1	29.5	28.0	28.6	28.5	29.0	29.5
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2					+ 0.2 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.2					+ 0.2 / - 0.3					

CIE Pub.117 Corrected 3427 lm Total Lamp Luminous Flux. (8log(F/F0) = 4.3)

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:31 August 2023

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.892m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:240.0V I:0.1615A P:37.11W PF:0.9577 Lamp Flux:3427.48x1 lm		
NAME: FLATLINE_1296_SUS_WHT_UPLIGHT_OPAL V_HE_500mA_4000K CRI90	WEIGHT:	
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	58	47	40	58	47	40	57	46	40	33
0.80	68	57	50	67	57	50	66	56	49	42
1.00	77	66	59	76	65	58	73	67	58	51
1.25	84	73	66	82	73	66	80	71	65	58
1.50	89	79	72	87	78	72	84	76	71	63
2.00	95	87	81	94	86	80	90	84	78	71
2.50	99	92	86	97	90	85	93	88	83	75
3.00	103	96	90	100	94	89	96	91	87	79
4.00	106	101	96	104	99	95	100	96	92	83
5.00	109	104	100	106	102	99	102	99	95	86
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JEFF
Test Date: 31 August 2023

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity: 65.0%
Test Distance: 7.892m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:240.0V I:0.1615A P:37.11W PF:0.9577 Lamp Flux:3427.48x1 lm		
NAME: FLATLINE_1296_SUS_WHT_UPLIGHT_OPAL V_HE_500mA_4000K CRI90	WEIGHT:	
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:31 August 2023

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.892m [K=1.0000]
Remarks:

AAI Figure

Test:U:240.0V I:0.1615A P:37.11W PF:0.9577 Lamp Flux:3427.48x1 lm		
NAME: FLATLINE_1296_SUS_WHT_UPLIGHT_OPAL V_HE_500mA_4000K CRI90	WEIGHT:	
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:31 August 2023

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.892m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:240.0V I:0.1615A P:37.11W PF:0.9577 Lamp Flux:3427.48x1 lm		
NAME: FLATLINE_1296_SUS_WHT_UPLIGHT_OPAL V_HE_500mA_4000K CRI90	WEIGHT:	
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:31 August 2023

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.892m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:240.0V I:0.1615A P:37.11W PF:0.9577 Lamp Flux:3427.48x1 lm		
NAME: FLATLINE_1296_SUS_WHT_UPLIGHT_OPAL V_HE_500mA_4000K CRI90		WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	22046
L_0~180 (75) av	18982
L_0~180 (85) av	11812
L_90~270 (65) av	21038
L_90~270 (75) av	18648
L_90~270 (85) av	15184
L_45 (65) av	21498
L_45 (75) av	18777
L_45 (85) av	14443

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:31 August 2023

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.892m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JEFF
Test Date: 31 August 2023

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity: 65.0%
Test Distance: 7.892m [K=1.0000]
Remarks:

