


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:239.8V I:0.1320A P:29.81W PF:0.9419 Lamp Flux:2756.14x1 lm		
NAME: WYN_1150_NA_WHT_HE_400mA_4000K CRI90	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 92.46 lm/W			
LED MODEL	1300lm 940 HV ADV6	Imax(cd)	989.6	S/MH(C0/180)	1.30
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.76
RATED VOLTAGE(V)	230.0	TOTAL FLUX(lm)	2756.1	η UP,DN(C0-180)	0.0,36.0
NOMINAL FLUX(lm)	2756.14	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,64.0
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	230	η down(%)	100.0	CIBSE SHR MAX	1.55

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:17 October 2024

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.888m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	804.9	753.0	733.7	752.7	804.2	862.1	888.3	862.7	0- 10	77.51	77.51	2.81,2.81
20	770.4	674.6	643.2	674.0	768.9	890.6	950.3	892.2	10- 20	225.4	302.9	11,11
30	713.8	583.8	546.1	583.0	711.4	902.5	989.6	905.5	20- 30	353.2	656.1	23.8,23.8
40	636.9	483.0	444.0	482.0	633.4	884.7	964.6	887.7	30- 40	446.0	1102	40,40
50	541.2	375.2	339.7	374.0	536.7	814.2	886.9	818.1	40- 50	489.5	1592	57.7,57.7
60	428.4	265.0	237.5	263.9	422.8	696.8	742.1	701.4	50- 60	476.0	2068	75,75
70	297.9	158.9	141.1	157.9	290.5	513.4	493.8	517.4	60- 70	397.4	2465	89.4,89.4
80	145.9	66.89	61.66	66.35	136.9	178.5	88.18	180.4	70- 80	238.3	2703	98.1,98.1
90	1.961	1.222	1.048	1.222	0.9106	0.6973	0.6891	0.7096	80- 90	52.81	2756	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1344.8 lm

%lum = 48.8%

%lamp = 48.8%

Conical surface Flux(120deg): 2067.6 lm

%lum = 75.0%


%lamp = 75.0%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JEFF
 Test Date:17 October 2024

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:65.0%
 Test Distance:7.888m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:239.8V I:0.1320A P:29.81W PF:0.9419 Lamp Flux:2756.14x1 lm		
NAME: WYN_1150_NA_WHT_HE_400mA_4000K CRI90	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	17165	7001
80	18716	7923
75	19309	8582
70	19401	9208
65	19266	9931
60	19084	10597
55	18910	11207
50	18753	11791
45	18621	12364


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:17 October 2024

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.888m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:239.8V I:0.1320A P:29.81W PF:0.9419 Lamp Flux:2756.14x1 lm		
NAME: WYN_1150_NA_WHT_HE_400mA_4000K CRI90	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.03	.98	.94	1.01	.97	.93	.96	.93	.90	.92	.90	.87	.89	.87	.84	.82
2.0	.89	.82	.76	.87	.80	.75	.83	.78	.73	.80	.75	.71	.77	.73	.70	.67
3.0	.77	.69	.62	.76	.68	.61	.73	.66	.60	.70	.64	.59	.67	.62	.58	.56
4.0	.68	.59	.52	.67	.58	.51	.64	.57	.51	.62	.55	.50	.59	.54	.49	.47
5.0	.60	.51	.44	.59	.50	.44	.57	.49	.43	.55	.48	.43	.53	.47	.42	.40
6.0	.54	.45	.38	.53	.44	.38	.51	.43	.38	.50	.43	.37	.48	.42	.37	.35
7.0	.49	.40	.33	.48	.39	.33	.46	.39	.33	.45	.38	.33	.44	.37	.32	.30
8.0	.44	.36	.30	.44	.35	.29	.42	.35	.29	.41	.34	.29	.40	.34	.29	.27
9.0	.41	.32	.26	.40	.32	.26	.39	.31	.26	.38	.31	.26	.37	.30	.26	.24
10.0	.37	.29	.24	.37	.29	.24	.36	.29	.24	.35	.28	.24	.34	.28	.23	.22



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:17 October 2024

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.888m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:239.8V I:0.1320A P:29.81W PF:0.9419 Lamp Flux:2756.14x1 lm		
NAME: WYN_1150_NA_WHT_HE_400mA_4000K CRI90	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.326	.186	.059	.319	.182	.058	.306	.176	.056	.294	.169	.054	.282	.164	.053		
2.0	.307	.168	.052	.301	.166	.051	.289	.161	.050	.278	.156	.049	.268	.151	.048		
3.0	.283	.151	.045	.277	.149	.045	.267	.145	.044	.257	.141	.043	.248	.137	.043		
4.0	.260	.135	.040	.255	.133	.039	.246	.130	.039	.237	.127	.038	.229	.124	.038		
5.0	.239	.122	.035	.235	.121	.035	.227	.118	.035	.219	.116	.034	.212	.113	.034		
6.0	.221	.111	.032	.217	.110	.032	.210	.108	.031	.203	.105	.031	.197	.103	.031		
7.0	.205	.101	.029	.202	.101	.029	.195	.099	.028	.189	.097	.028	.183	.095	.028		
8.0	.191	.093	.026	.188	.093	.026	.182	.091	.026	.177	.089	.026	.171	.088	.026		
9.0	.179	.086	.024	.176	.086	.024	.171	.084	.024	.166	.083	.024	.161	.082	.024		
10.0	.168	.080	.022	.165	.080	.022	.160	.079	.022	.156	.077	.022	.152	.076	.022		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)										
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020		
1.0	.181	.156	.133	.155	.134	.115	.106	.092	.079	.061	.053	.046	.020	.017	.015		
2.0	.174	.132	.096	.149	.113	.083	.102	.079	.058	.059	.046	.034	.019	.015	.011		
3.0	.167	.114	.072	.143	.099	.063	.098	.069	.044	.057	.040	.026	.018	.013	.009		
4.0	.160	.101	.057	.137	.087	.049	.094	.061	.035	.054	.036	.021	.018	.012	.007		
5.0	.152	.091	.046	.131	.079	.040	.090	.055	.028	.052	.032	.017	.017	.011	.006		
6.0	.145	.083	.038	.124	.072	.033	.086	.050	.023	.050	.029	.014	.016	.010	.005		
7.0	.138	.076	.032	.119	.066	.028	.082	.046	.020	.048	.027	.012	.015	.009	.004		
8.0	.131	.070	.028	.113	.061	.024	.078	.043	.017	.045	.025	.010	.015	.008	.003		
9.0	.125	.065	.025	.108	.056	.021	.075	.040	.015	.043	.023	.009	.014	.008	.003		
10.0	.119	.061	.022	.103	.053	.019	.071	.037	.014	.042	.022	.008	.013	.007	.003		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:17 October 2024

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.888m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:239.8V I:0.1320A P:29.81W PF:0.9419 Lamp Flux:2756.14x1 lm										
NAME: WYN_1150_NA_WHT_HE_400mA_4000K CRI90					TYPE:LED			WEIGHT:		
SPEC.:					DIM.:			SERIAL No.:1		
MFR.: DARKON					SUR.:			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	21.7	23.3	22.0	23.5	23.7	19.6	21.2	19.9	21.4	21.6
3H	23.6	25.1	23.9	25.3	25.6	20.9	22.3	21.2	22.6	22.8
4H	24.5	25.9	24.8	26.2	26.4	21.4	22.8	21.7	23.0	23.3
6H	25.2	26.5	25.6	26.8	27.1	21.8	23.1	22.1	23.4	23.7
8H	25.5	26.8	25.8	27.1	27.3	21.9	23.2	22.3	23.5	23.8
12H	25.7	26.9	26.0	27.2	27.5	22.0	23.2	22.4	23.5	23.8
4H 2H	22.0	23.4	22.3	23.6	23.9	20.3	21.7	20.6	21.9	22.2
3H	24.0	25.2	24.4	25.5	25.8	21.7	23.0	22.1	23.3	23.6
4H	25.0	26.1	25.3	26.4	26.8	22.4	23.5	22.7	23.8	24.1
6H	25.8	26.8	26.2	27.2	27.5	22.9	23.9	23.3	24.2	24.6
8H	26.1	27.1	26.6	27.5	27.8	23.1	24.0	23.5	24.4	24.8
12H	26.4	27.3	26.8	27.7	28.1	23.2	24.0	23.6	24.4	24.8
8H 4H	25.0	26.0	25.5	26.4	26.7	22.7	23.6	23.1	24.0	24.4
6H	26.0	26.8	26.4	27.2	27.6	23.3	24.1	23.8	24.5	25.0
8H	26.4	27.1	26.8	27.5	27.9	23.6	24.3	24.1	24.7	25.2
12H	26.7	27.3	27.2	27.8	28.2	23.8	24.4	24.3	24.9	25.3
12H 4H	25.0	25.9	25.5	26.3	26.7	22.7	23.6	23.2	24.0	24.4
6H	26.0	26.7	26.5	27.1	27.6	23.4	24.1	23.9	24.5	25.0
8H	26.4	27.0	26.9	27.5	27.9	23.7	24.3	24.2	24.8	25.3
Variations with the observer position at spacings:										
S = 1.0H	+ 0.1 / - 0.1					+ 0.2 / - 0.2				
1.5H	+ 0.3 / - 0.3					+ 0.2 / - 0.3				
2.0H	+ 0.7 / - 0.7					+ 0.2 / - 0.3				

CIE Pub.117 Corrected 2756 lm Total Lamp Luminous Flux. (8log(F/F0) = 3.5)

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:17 October 2024

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.888m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:239.8V I:0.1320A P:29.81W PF:0.9419 Lamp Flux:2756.14x1 lm		
NAME: WYN_1150_NA_WHT_HE_400mA_4000K CRI90	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	55	43	36	54	43	35	53	42	35	29
0.80	65	53	45	64	52	45	62	52	44	37
1.00	73	62	54	72	61	54	70	63	53	46
1.25	81	70	62	79	69	62	76	67	61	53
1.50	86	75	68	84	75	68	81	73	66	59
2.00	93	84	77	91	83	77	88	81	75	67
2.50	97	89	83	95	88	82	91	85	80	71
3.00	101	94	88	99	92	87	95	89	85	76
4.00	105	99	94	103	98	93	99	94	90	81
5.00	108	103	99	106	101	97	101	97	94	85
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:17 October 2024

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.888m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:239.8V I:0.1320A P:29.81W PF:0.9419 Lamp Flux:2756.14x1 lm		
NAME: WYN_1150_NA_WHT_HE_400mA_4000K CRI90	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:17 October 2024

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.888m [K=1.0000]
Remarks:

AAI Figure

Test:U:239.8V I:0.1320A P:29.81W PF:0.9419 Lamp Flux:2756.14x1 lm		
NAME: WYN_1150_NA_WHT_HE_400mA_4000K CRI90	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:17 October 2024

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.888m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:239.8V I:0.1320A P:29.81W PF:0.9419 Lamp Flux:2756.14x1 lm		
NAME: WYN_1150_NA_WHT_HE_400mA_4000K CRI90	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:17 October 2024

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.888m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:239.8V I:0.1320A P:29.81W PF:0.9419 Lamp Flux:2756.14x1 lm		
NAME: WYN_1150_NA_WHT_HE_400mA_4000K CRI90	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: DARKON	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	19139
L_0~180 (75) av	18988
L_0~180 (85) av	16163
L_90~270 (65) av	21785
L_90~270 (75) av	17089
L_90~270 (85) av	8558
L_45 (65) av	21857
L_45 (75) av	21018
L_45 (85) av	9226

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JEFF
Test Date:17 October 2024

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.888m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JEFF
Test Date: 17 October 2024

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity: 65.0%
Test Distance: 7.888m [K=1.0000]
Remarks:

