



SUITABLE FOR GRID SIZE

- 595 (L) x 295 (W)
- 1195 (L) x 295 (W)
- 595 (L) x 595 (W)



DESIGN FEATURES

- Cost effective commercial office tenancy lighting solution
- Dual light source delivers high output
- Large luminous opening provides low unified glare ratio and high visual comfort
- Locally produced and robust construction utilising Australian sheet metal and aluminium extrusion
- Multiple fixed output options
- Zhaga compliant LED
- 111 exit lumens per system watt
- 80+ or 90+ colour rendering
- High colour tolerance Macadam 3
- Complies with AS/NZS 60598.2.1
- L80 / F10 = 72,000 hours @ 450mA / 75°C TA

INSTALLATION FEATURES

- T-bar ceiling integration
- Detailed shop drawings
- Australian made
- Supplied 100% pre-built
- Removable gear tray
- Integral mounted driver
- 5 year warranty
- 10 year extended warranty optional
- Project specific labelling referencing type numbers

LUMEN PERFORMANCE

TRIDONIC LLE24 FIXED WHITE G5 LED

HE	100mA	11 W	1127 lm
HE	150mA	16 W	1680 lm
HE	200mA	20 W	2218 lm
HE	250mA	25 W	2778 lm
HE	300mA	30 W	3319 lm
HE	350mA	36 W	3810 lm

SYSTEM WATTAGE & EXIT LUMENS
TESTED WITH OPAL VL2 / WHITE FINISH / 4000K

CONFIGURATOR

- FINISH:** White
- LENS:** Opal VL2
- LED:** HE
- CURRENT:** 100mA / 150mA / 200mA /
- CURRENT:** 250mA / 300mA / 350mA
- COLOUR TEMP:** 2700K / 3000K / 4000K
- DIMMING:** Non Dim / DALI / DSI / Switch Dim