



















DESIGN FEATURES

- Opal diffuser for low glare applications
- Minimal trim for a 'trim-less' appearance
- 104 exit lumens per system watt
- 80+ colour rendering
- High colour tolerance Macadam 3 Complies with AS/NZS 60598.2.1
- L80 / F10 = 40,000 hours @ 700mA / 75°C TP

INSTALLATION FEATURES

- Removable internal assembly for ease of maintenance
- Australian designed and assembled Supplied 100% pre-built
- 5 year warranty
- 10 year extended warranty optional Project specific labelling referencing type numbers
- Easy to follow install guide

LUMEN PERFORMANCE

TRIDONIC CLE 315mm LED

900mA 31.3 W 3244 lm

SYSTEM WATTAGE / EXIT LUMENS @ 4000K

OPTIONS

FINISH INT: White / Black FINISH EXT: White / Black **CEILING PLATE FINISH: White / Black**

CEILING PLATE TYPE: Surface Mounted / Recessed

SUSPENSION TYPE: 2m wire / 4m wire CURRENT: 900mA

COLOUR TEMP: 3000K / 4000K **DIMMING:** Non Dim / DALI / DSI / Switch Dim

PROJECT: TYPE NO.: QTY:

REV: 08/12/20 DARKON.COM.AU