DEEP DOWN SM RTSURFACE MOUNTED LUMINAIRES
















DESIGN FEATURES

- Recessed lamp for low glare applications
- Surface mounted tube allows two tone finish
- COB LED achieves a single light source appearance
- Up to 95 exit lumens per system watt
- 80+ colour rendering
- Small colour tolerance MacAdam 3
- Complies with AS/NZS 60598.2.1
- L80 / B10 = 55,000 hours @ 250mA / 65°C TP
- L80 / B10 = 55,000 hours @ 350mA / 65°C TP

INSTALLATION FEATURES

- Australian designed and assembled
- Supplied 100% pre-built
- 5 year warranty
- 10 year extended warranty optional
- · Project specific labelling referencing type numbers
- Easy to follow install guide

LUMEN PERFORMANCE

TRIDONIC SLE 09MM G7 ADV LED

250mA 10.4 W 989 lm 350mA 14.2 W 1312 lm

SYSTEM WATTAGE / EXIT LUMENS @ 50° / 4000K

OPTIONS

FINISH EXT: White / Black
FINISH INT: White / Black
CURRENT: 250mA / 350mA
COLOUR TEMP: 3000K / 4000K
OPTIC: 24° / 32° / 50°

DIMMING: Non Dim / Phase Dim /

DALI / DSI / Switch Dim

FLEX: Flex & plug / No flex & plug

PROJECT: TYPE NO.: QTY:

REV: 30/09/21 DARKON.COM.AU