
# **GRAZER IP1616 SM** SURFACE MOUNTED PROFILES




P67





30





# **DESIGN FEATURES**

- Utilises silicone Neon LED .
- ٠ In-house Neon LED length customisation
- In-house Neon LED moulded end caps •
- IP67 ingress protection ٠
- Dot free homogeneous illumination
- Dust free matt finish silicone
- Multiple fixed output options
- Up to 92 exit lumens per system watt
- . 90+ colour rendering
- 10m max single length of LED with single power feed (White)
- 5m max single length of LED with single power feed (TW / RGB/W)
- . Max single length doubles with dual power feed option
- . UV protected

## LUMEN PERFORMANCE

### T1616 NEON LED

20.1 W p/mtr 1584 lm p/mtr

SYSTEM WATTAGE & EXIT LUMENS TESTED WITH WHITE FINISH AT 4000K

#### Screwless end caps

- Complies with AS/NZS 60598.2.1 •
- 50,000 hrs lifetime
- L70B50 > 50.000 hrs
- 3 year warranty
- · Project specific labelling referencing type numbers
- Detailed shop drawings
- Miter joins are not available

### CONFIGURATOR

INT FINISH: White / Black / Silver / Gold / Custom EXT FINISH: White / Black / Silver / Gold / Custom COLOUR TEMP: 2700K / 3000K / 4000K / TW / RGB / RGBW DRIVER: Non Dim / DALI Dim / DMX