



DESIGN FEATURES

- Dot free homogeneous illumination
- Multiple fixed output options
- Up to 86 exit lumens per system watt
- 90+ colour rendering, 80+ available upon request
- High colour tolerance - MacAdam 3
- Complies with AS/NZS 60598.2.1

INSTALLATION FEATURES

- Detailed shop drawings
- Australian made
- Supplied 100% pre-built
- 5 year warranty
- 10 year extended warranty optional
- Project specific labelling referencing type numbers
- Approximate fitting weight of 1.1 Kg per/m.
- Miter joints are not available

LUMEN PERFORMANCE

TRIDONIC FIXED WHITE / EXIT LUMENS

HE CRI90	200mA	1117 lm p/mtr	13 W p/mtr
HE CRI90	250mA	1380 lm p/mtr	16 W p/mtr
HE CRI90	300mA	1632 lm p/mtr	19 W p/mtr
HE CRI90	350mA	1879 lm p/mtr	22 W p/mtr
HE CRI90	400mA	2115 lm p/mtr	26 W p/mtr
HE CRI90	450mA	2330 lm p/mtr	29 W p/mtr
HE CRI90	500mA	2549 lm p/mtr	32 W p/mtr

DPAL TAPE / EXIT LUMENS

DPAL20	24V	313 lm p/mtr	8 W p/mtr
DPAL60	24V	313 lm p/mtr	18 W p/mtr

Tested with white finish @ 4000K with Opal V lens.

CONFIGURATOR

INT FINISH: Black / White / Silver

EXT FINISH: Black / White / Silver

CEILING PLATE FINISH: White / Black

CEILING PLATE TYPE: Surface mounted / Recessed

SUSPENSION TYPE: 2m wire / 4m wire

LENS: Opal V

LED: HE / DPAL20 / DPAL60 / RGBW HE / RGBW HO

CURRENT DOWN: 200 / 250 / 300 / 350 / 400 / 450 / 500mA

TEMP: 2700K / 3000K / 4000K

DIMMING: Non dim / DALI dim / SwitchDIM / DSI dim

PROJECT:

TYPE NO:

QTY:

REV: 1/06/2023

DARKON.COM.AU