HIP H LP SUS SUSPENDED PROFILE





DESIGN FEATURES

- •Dot free homogeneous illumination.
- •Screwless end caps.
- Multiple fixed output options.
- Multiple snap fit lens options.
- •Zhaga compliant.
- Up to 119 exit lumens per system watt.
- •80+ or 90+ colour rendering.
- •High colour tolerance MacAdam 3.
- •L80 / F10 = 72,000 hours @ 450mA / 75°C TA
- •Complies with AS/NZS 60598.2.1

INSTALLATION FEATURES

- Detailed shop drawings.
- •Australian made.
- •Supplied 100% pre-built.
- •Snap fit gear tray with integrated driver.
- Plug and play wire looms.
- •Sprung loaded control joints
- •5 year warranty.
- •10 year extended warranty optional.
- Project specific labelling referencing type numbers.

LUMEN PERFORMANCE

TRIDONIC FIXED WHITE / EXIT LUMENS (DIRECT)

HE	350mA	1796 lm p/mtr	16 W p/mtr
HE	400mA	2059 lm p/mtr	18 W p/mtr
HE	450mA	2298 lm p/mtr	21 W p/mtr
HE	500mA	2507 lm p/mtr	23 W p/mtr
HO	350mA	3582 lm p/mtr	30 W p/mtr
HO	400mA	4106 lm p/mtr	35 W p/mtr
HO	450mA	4482 lm p/mtr	39 W p/mtr
HO	500mA	4869 lm p/mtr	43 W p/mtr
TRIDONIC FIXED WHITE / EXIT LUMENS (INDIRECT)			
HE	200mA	1036 lm p/mtr	10 W p/mtr
HE	250mA	1276 lm p/mtr	12 W p/mtr
HE	300mA	1534 lm p/mtr	14 W p/mtr
HE	350mA	1759 lm p/mtr	16 W p/mtr
HE	400mA	2014 lm p/mtr	18 W p/mtr
HO	200mA	2100 lm p/mtr	18 W p/mtr
HO	250mA	2582 lm p/mtr	22 W p/mtr
HO	300mA	3066 lm p/mtr	26 W p/mtr
HO	350mA	3507 lm p/mtr	30 W p/mtr
НО	400mA	4007 lm p/mtr	35 W p/mtr

PROJECT: REV: 17/02/2021

FINISH: Black / White / Silver

CONFIGURATOR

CEILING PLATE FINISH: White / black CEILING PLATE TYPE: Surface mounted / Recessed SUSPENSION TYPE: 2m wire / 4m wire LENS DOWN: Opal V / Deglaring / Asymmetric / Narrow LENS UP Opal V / Deglaring / Asymmetric / Narrow LED DOWN: HE / HO / Tunable white (2700K-6500K) CURRENT DOWN: 350 / 400 / 450 / 500mA LED UP: HE / HO / Tunable white (2700K-6500K) CURRENT UP: 200 / 250 / 300 / 350 / 400mA TEMP: 2700K / 3000K / 4000K CIRCUIT: Single circuit / Dual circuit

DIMMING: Non Dim / Dali Dim / Switch Dim / Dsi Dim

TYPE NO: