



HIP RADII RING SUS

SUSPENDED PROFILES


DARKON

THE EDGE OF LIGHT



ø805 / 1160 / 1516 / 1872

RINGS ARE FABRICATED FROM MULTIPLE PIECES & WELDED TOGETHER FOR A SEAMLESS FINISH.
CUSTOM SIZE REQUIRES TOOLING FEE.



DESIGN FEATURES

- Custom sizes available with tooling fee
- Dot free homogeneous illumination
- Multiple fixed output options
- Zhaga compliant LED
- Up to 105 exit lumens per system watt
- 90+ colour rendering, 80+ available upon request
- High colour tolerance Macadam 3
- Complies with AS/NZS 60598.2.1
- L80 / F10 = 72,000 hours @ 450mA / 75°C TA

INSTALLATION FEATURES

- Detailed shop drawings
- Australian made
- Supplied 100% pre-built
- Plug and Play wire looms
- 5 year warranty
- 10 year extended warranty optional
- Project specific labelling referencing type numbers

LUMEN PERFORMANCE

TRIDONIC LLE24 FIXED WHITE G5 LED

HE	200mA	10 W p/mtr	885 lm p/mtr
HE	250mA	12 W p/mtr	1098 lm p/mtr
HE	300mA	14 W p/mtr	1306 lm p/mtr
HE	350mA	16 W p/mtr	1509 lm p/mtr
HE	400mA	18 W p/mtr	1709 lm p/mtr
HE	450mA	20 W p/mtr	1906 lm p/mtr
HE	500mA	23 W p/mtr	2107 lm p/mtr
HO	200mA	17 W p/mtr	1781 lm p/mtr
HO	250mA	21 W p/mtr	2197 lm p/mtr
HO	300mA	25 W p/mtr	2601 lm p/mtr
HO	350mA	29 W p/mtr	2992 lm p/mtr
HO	400mA	33 W p/mtr	3370 lm p/mtr
HO	450mA	37 W p/mtr	3665 lm p/mtr
HO	500mA	42 W p/mtr	4017 lm p/mtr

SYSTEM WATTAGE & EXIT LUMENS
TESTED WITH OPAL V / WHITE FINISH / 4000K

CONFIGURATOR

- FINISH:** White / black
CEILING PLATE FINISH: White / black
CEILING PLATE TYPE: Surface Mounted / Recessed
SUSPENSION TYPE: 2m Wire / 4m Wire
LENS: Opal V
LED: HE / HO / Tunable white (2700K-6500K)
CURRENT: 200 / 250 / 300 / 350 / 400 / 450 / 500mA
COLOUR TEMP: 2700K / 3000K / 4000K
DIMMING: Non Dim / DALI / DSI / Switch Dim
- NOTES:** Ø805MM REQUIRES REMOTE DRIVER

PROJECT:

TYPE NO.:

QTY:

REV: 23/04/24

DARKON.COM.AU