




HIP TRIM RADII RING REC

RECESSED PROFILES

DARKON

THE EDGE OF LIGHT



ø814 / 1170 / 1526 / 1882

RINGS ARE FABRICATED FROM MULTIPLE PIECES & WELDED TOGETHER FOR A SEAMLESS FINISH.
CUSTOM SIZE REQUIRES TOOLING FEE.

CUT OUT



USE RING AS GUIDE
FOR CUTOUT



INTEGRAL
DRIVER

DESIGN FEATURES

- Custom sizes available with tooling fee
- Dot free homogeneous illumination
- Multiple fixed output options
- Zhaga compliant LED
- Up to 108 exit lumens per system watt
- 90+ colour rendering, 80+ available upon request
- High colour tolerance Macadam 3
- Complies with AS/NZS 60598.2.1
- L80 / F10 = 72,000 hours @ 450mA / 75°C TA
- Detailed shop drawings
- Australian made
- Supplied 100% pre-built
- Plug and Play wire looms
- 5 year warranty
- 10 year extended warranty optional
- Project specific labelling referencing type numbers

LUMEN PERFORMANCE

TRIDONIC LLE24 FIXED WHITE LED

HE	200mA	10 W p/mtr	905 lm p/mtr
HE	250mA	12 W p/mtr	1122 lm p/mtr
HE	300mA	14 W p/mtr	1335 lm p/mtr
HE	350mA	16 W p/mtr	1544 lm p/mtr
HE	400mA	19 W p/mtr	1748 lm p/mtr
HE	450mA	21 W p/mtr	1949 lm p/mtr
HE	500mA	23 W p/mtr	2154 lm p/mtr
HO	200mA	17 W p/mtr	1821 lm p/mtr
HO	250mA	21 W p/mtr	2247 lm p/mtr
HO	300mA	25 W p/mtr	2659 lm p/mtr
HO	350mA	30 W p/mtr	3059 lm p/mtr
HO	400mA	34 W p/mtr	3446 lm p/mtr
HO	450mA	38 W p/mtr	3747 lm p/mtr
HO	500mA	43 W p/mtr	4107 lm p/mtr

SYSTEM WATTAGE & EXIT LUMENS

TESTED WITH OPAL V / WHITE FINISH / 4000K

OPTIONS

FINISH: White / black

LENS: Opal V

LED: HE / HO / Tunable white (2700K-6500K)

CURRENT: 200 / 250 / 300 / 350 / 400 / 450 / 500mA

COLOUR TEMP: 2700K / 3000K / 4000K

DIMMING: Non Dim / DALI / DSI / Switch Dim

NOTES: Ø814MM REQUIRES REMOTE DRIVER

PROJECT:

TYPE NO.:

QTY:

REV: 07/11/25

DARKON.COM.AU