



DESIGN FEATURES

- Dot free homogeneous illumination.
- Screwless end caps.
- Multiple fixed output options.
- Multiple snap fit lens options.
- Zhaga compliant.
- Up to 94 exit lumens per system watt.
- 80+ or 90+ colour rendering.
- High colour tolerance - MacAdam 3.
- L80 / F10 = 72,000 hours @ 450mA / 75°C TA
- Complies with AS/NZS 60598.2.1

INSTALLATION FEATURES

- Detailed shop drawings.
- Australian made.
- Supplied 100% pre-built.
- Snap fit gear tray with integrated driver.
- Plug and play wire looms.
- Sprung loaded control joints
- 5 year warranty.
- 10 year extended warranty optional.
- Project specific labelling referencing type numbers.
- Miter joints available on request.
- Welded mitre joints eliminate light bleed.

LUMEN PERFORMANCE

TRIDONIC FIXED WHITE / EXIT LUMENS (DIRECT)				
HE	350mA	1413 lm p/mtr	16 W p/mtr	
HE	400mA	1617 lm p/mtr	18 W p/mtr	
HE	450mA	1802 lm p/mtr	21 W p/mtr	
HE	500mA	1973 lm p/mtr	23 W p/mtr	
HO	350mA	2817 lm p/mtr	30 W p/mtr	
HO	400mA	3218 lm p/mtr	35 W p/mtr	
HO	450mA	3555 lm p/mtr	39 W p/mtr	
HO	500mA	3870 lm p/mtr	43 W p/mtr	
TRIDONIC FIXED WHITE / EXIT LUMENS (INDIRECT)				
HE	200mA	1478 lm p/mtr	13 W p/mtr	
HE	250mA	1824 lm p/mtr	16 W p/mtr	
HE	300mA	2184 lm p/mtr	20 W p/mtr	
HE	350mA	2502 lm p/mtr	23 W p/mtr	
HE	400mA	2850 lm p/mtr	26 W p/mtr	
HE	450mA	3150 lm p/mtr	30 W p/mtr	
HE	500mA	3440 lm p/mtr	33 W p/mtr	

Tested with white finish @ 4000K with opal v lens.

CONFIGURATOR

FINISH:	Black / White / Silver
CEILING PLATE FINISH:	White / black
CEILING PLATE TYPE:	Surface mounted / Recessed
SUSPENSION TYPE:	2m wire / 4m wire
DOWN LENS:	Opal V / Deglaring / Asymmetric
LED DOWN:	HE / HO / Tunable white (2700K-6500K)
CURRENT DOWN:	350 / 400 / 450 / 500mA
LED UP:	HE
CURRENT UP:	200 / 250 / 300 / 350 / 400 / 450 / 500mA
TEMP:	2700K / 3000K / 4000K
CIRCUIT:	Single circuit / Dual circuit
DIMMING:	Non Dim / Dali Dim / Switch Dim / Dsi Dim

PROJECT:

TYPE NO:

QTY:

REV: 16/10/2020

DARKON.COM.AU