



SLIM C UP WALL


WALL MOUNTED PROFILE

DARKON

THE EDGE OF LIGHT



49



INTEGRAL DRIVER

DESIGN FEATURES

- Dot free homogeneous illumination
- Multiple fixed output options
- Multiple snap fit lens options
- Zhaga compliant
- Up to 100 exit lumens per system watt
- 90+ colour rendering, 80+ available upon request
- High colour tolerance - MacAdam 3
- L80 / F10 = 72,000 hours @ 450mA / 75°C TA
- Complies with AS/NZS 60598.2.1
- Lap join milling - No Light Bleed

INSTALLATION FEATURES

- Detailed shop drawings
- Australian made
- Supplied 100% pre-built
- 5 year warranty
- 10 year extended warranty optional
- Project specific labelling referencing type numbers
- Miter joints available
- Welded mitre joints eliminate light bleed

LUMEN PERFORMANCE

TRIDONIC FIXED WHITE / EXIT LUMENS (INDIRECT)

| | | | |
|----------|-------|---------------|------------|
| HE CRI90 | 200mA | 845 lm p/mtr | 10 W p/mtr |
| HE CRI90 | 250mA | 1048 lm p/mtr | 12 W p/mtr |
| HE CRI90 | 300mA | 1246 lm p/mtr | 14 W p/mtr |
| HE CRI90 | 350mA | 1441 lm p/mtr | 16 W p/mtr |
| HE CRI90 | 400mA | 1631 lm p/mtr | 18 W p/mtr |
| HE CRI90 | 450mA | 1817 lm p/mtr | 20 W p/mtr |
| HE CRI90 | 500mA | 2008 lm p/mtr | 23 W p/mtr |
| HO CRI90 | 200mA | 1697 lm p/mtr | 17 W p/mtr |
| HO CRI90 | 250mA | 2094 lm p/mtr | 21 W p/mtr |
| HO CRI90 | 300mA | 2479 lm p/mtr | 25 W p/mtr |
| HO CRI90 | 350mA | 2852 lm p/mtr | 29 W p/mtr |
| HO CRI90 | 400mA | 3212 lm p/mtr | 33 W p/mtr |
| HO CRI90 | 450mA | 3493 lm p/mtr | 37 W p/mtr |
| HO CRI90 | 500mA | 3828 lm p/mtr | 42 W p/mtr |

Tested with white finish @ 4000K.

CONFIGURATOR

FINISH: Black / White / Silver

LENS UP: Opal V / Deglaring / Asymmetric / Narrow

LED UP: HE / HO / Tunable white

CURRENT UP: 200 / 250 / 300 / 350 / 400 / 450 / 500mA

TEMP: 2700K / 3000K / 4000K

DIMMING: Non dim / DALI / SwitchDIM / DSI

PROJECT:

TYPE NO:

QTY:

REV: 8/03/2023

DARKON.COM.AU