




TRIM RADII RING REC

RECESSED PROFILES


DARKON

THE EDGE OF LIGHT



∅866 / 1224 / 1582 / 1938

RINGS ARE FABRICATED FROM MULTIPLE PIECES & WELDED TOGETHER FOR A SEAMLESS FINISH.
CUSTOM SIZE REQUIRES TOOLING FEE.



DESIGN FEATURES

- Custom radius available
- Dot free homogeneous illumination
- Multiple fixed output options
- Zhaga compliant LED
- Up to 83 exit lumens per system watt
- 80+ or 90+ colour rendering
- High colour tolerance Macadam 3
- Complies with AS/NZS 60598.2.1
- L80 / F10 = 72,000 hours @ 450mA / 75°C TA

INSTALLATION FEATURES

- Detailed shop drawings
- Australian made
- Supplied 100% pre-built
- Plug and Play wire looms
- 5 year warranty
- 10 year extended warranty optional
- Project specific labelling referencing type numbers

LUMEN PERFORMANCE

TRIDONIC LLE24 FIXED WHITE G5 LED

HE	350mA	16 W p/mtr	1256 lm p/mtr
HE	400mA	18 W p/mtr	1438 lm p/mtr
HE	450mA	21 W p/mtr	1602 lm p/mtr
HE	500mA	23 W p/mtr	1755 lm p/mtr
HO	350mA	30 W p/mtr	2504 lm p/mtr
HO	400mA	35 W p/mtr	2861 lm p/mtr
HO	450mA	39 W p/mtr	3160 lm p/mtr
HO	500mA	43 W p/mtr	3441 lm p/mtr

SYSTEM WATTAGE & EXIT LUMENS
TESTED WITH OPAL V / WHITE FINISH / 4000K

CONFIGURATOR

FINISH: White / black
LENS: Opal V
LED: HE / HO / Tunable white (2700K-6500K)
CURRENT: 350mA / 400mA / 450mA / 500mA
COLOUR TEMP: 2700K* / 3000K / 4000K
DIMMING: Non Dim / DALI / DSI / Switch Dim

NOTES: ∅866MM REQUIRES REMOTE DRIVER
2700K AVAILABLE FOR SIZES ∅1582 AND OVER

PROJECT:

TYPE NO.:

QTY:

REV: 08/10/20

DARKON.COM.AU