



WYN IP SUS EDGE

SUSPENDED PROFILES

DARKON

THE EDGE OF LIGHT



DESIGN FEATURES

- Dot free homogeneous illumination
- Screwless end caps
- Multiple fixed output options
- Zhaga compliant LED
- High exit lumens per watt
- 80+ or 90+ colour rendering
- High colour tolerance Macadam 3
- Complies with AS/NZS 60598.2.1
- L80 / F10 = 72,000 hours @ 450mA / 75°C TA
- Detailed shop drawings
- Australian made
- Supplied 100% pre-built
- 5 year warranty
- 10 year extended warranty optional
- Project specific labelling referencing type numbers

LUMEN PERFORMANCE

TRIDONIC LLE24 FIXED WHITE G5 LED

HE	200mA	13 W p/mtr	1089 lm p/mtr
HE	250mA	16 W p/mtr	1345 lm p/mtr
HE	300mA	20 W p/mtr	1610 lm p/mtr
HE	350mA	23 W p/mtr	1845 lm p/mtr
HE	400mA	26 W p/mtr	2100 lm p/mtr
HE	450mA	30 W p/mtr	2321 lm p/mtr
HE	500mA	33 W p/mtr	2536 lm p/mtr
HO	200mA	17 W p/mtr	1476 lm p/mtr
HO	250mA	22 W p/mtr	1846 lm p/mtr
HO	300mA	26 W p/mtr	2206 lm p/mtr
HO	350mA	30 W p/mtr	2521 lm p/mtr
HO	400mA	34 W p/mtr	2866 lm p/mtr
HO	450mA	39 W p/mtr	3204 lm p/mtr
HO	500mA	43 W p/mtr	3482 lm p/mtr

SYSTEM WATTAGE & EXIT LUMENS
TESTED WITH OPAL V / WHITE FINISH / 4000K

CONFIGURATOR

- FINISH:** White / Black / Silver
- CEILING PLATE FINISH:** White / Black
- CEILING PLATE TYPE:** Surface mounted / Recessed
- SUSPENSION TYPE:** 2m wire / 4m wire / White rod / Black rod
- LENS:** Clear Lens
- LED:** HE / HO / DPAL20 / DPAL60 / RGBW HE / RGBW HO
- CURRENT:** 200 / 250 / 300 / 350 / 400 / 450 / 500mA
- HE/HO TEMP:** 2700K / 3000K / 4000K
- DPAL TEMP:** 3000K / 4000K
- DIMMING:** Non Dim / DALI / DSI / Switch Dim

PROJECT:

TYPE NO.:

QTY:

REV: 02/09/24

DARKON.COM.AU