

## DESIGN FEATURES

- Dot free homogeneous illumination.
- Screwless end caps.
- Multiple fixed output options.
- Multiple snap fit lens options.
- Up to 100 exit lumens per system watt.
- 80+ or 90+ colour rendering.
- High colour tolerance - MacAdam 3.
- Complies with AS/NZS 60598.2.1

## INSTALLATION FEATURES

- Detailed shop drawings.
- Australian made.
- Supplied 100% pre-built.
- 5 year warranty.
- 10 year extended warranty optional.
- Project specific labelling referencing type numbers.

## LUMEN PERFORMANCE

### TRIDONIC FIXED WHITE / EXIT LUMENS

HE	200mA	Pending test results	
HE	250mA	1543 lm p/mtr	16 W p/mtr
HE	300mA	1848 lm p/mtr	20 W p/mtr
HE	350mA	2116 lm p/mtr	23 W p/mtr
HE	400mA	2410 lm p/mtr	26 W p/mtr
HE	450mA	2664 lm p/mtr	30 W p/mtr
HE	500mA	2910 lm p/mtr	33 W p/mtr
HO	200mA	1694 lm p/mtr	17 W p/mtr
HO	250mA	2119 lm p/mtr	22 W p/mtr
HO	300mA	2531 lm p/mtr	26 W p/mtr
HO	350mA	2892 lm p/mtr	30 W p/mtr
HO	400mA	3289 lm p/mtr	34 W p/mtr
HO	450mA	3677 lm p/mtr	39 W p/mtr
HO	500mA	3996 lm p/mtr	43 W p/mtr

### DPAL TAPE / EXIT LUMENS

DPAL20	24V	337 lm p/mtr	8 W p/mtr
DPAL60	24V	728 lm p/mtr	18 W p/mtr

Tested with white finish @ 4000K.

## CONFIGURATOR

**MOUNTING:** Surface mounted / Edge (see page two)

**FINISH:** Black / White / Silver

**LED:** HE / HO / DPAL20 / DPAL60 / RGBW HE / RGBW HO

**CURRENT DOWN:** 200 / 250 / 300 / 350 / 400 / 450 / 500mA

**HE / HO TEMP:** 2700K / 3000K / 4000K

**DPAL TEMP:** 3000K / 4000K

**DIMMING:** Non Dim / Dali Dim / Switch Dim / Dsi Dim

PROJECT:


REV: 23/04/2021

TYPE NO:

QTY:

DARKON.COM.AU

## SURFACE MOUNT ORIENTATIONS



## EDGE MOUNT ORIENTATIONS

